

ALL IN ONE SOLAR STREET LIGHT



■ ALL IN ONE - 40W

Detail				Picture
Power	Specifications			
40W	Solar Panel	Max Power	18V/70W (High-efficiency monocrystalline solar panel)	
		Lifespan	25 years	
	Battery	Model	12.6V/26.4AH Lithium battery Cycle Times: 1000 times	
		Lifespan	5-8 years	
	LED Chip	Power	50W (Philips chip, Aluminum PCB Plate)	
		Chip brand	Philips SMD3030	
		Lumen	100-110lm/W	
		Lifespan	6 - 8 years	
	Install distance	Install height : 5-7M Install horizontal spacing : 15-20M		
	Install position	Light pole branch diameter : 60-100mm		
	Install body material	Aluminium alloy		
	Charging time	6 hours of effectively sun light		
	Working time	Light 10 to 12 hours every day, sustainable 3-7 rainy day		
	Switching mode	Time control + Light sensor control + motion sensor control		
	Certification	CE. ROHS		
	Size	Product size : L1150*300*H90mm Packing Size : 122*34.5*15.5cm 1pcs/carton		
Weight	Net weight : 13KG Gross weight : 14KG			
Warranty	5 years warranty			

■ ALL IN ONE - 100W

Detail				Picture
Power	Specifications			
100W	Solar Panel	Max Power	18V/70W (High-efficiency monocrystalline solar panel)	
		Lifespan	25 years	
	Battery	Model	25.2V, 40AH 18650 Lithium battery	
		Lifespan	1000 years	
	LED Chip	Power	192pcs (Philips chip, Aluminum PCB plate)	
		Chip brand	Philips SMD3030 CCT:2700-6500K	
		Lumen	160lm/w	
		Lifespan	6 - 8 years	
	Install distance	Install height : 8-10M Install horizontal spacing : 25-30M		
	Install position	Light pole branch diameter : 60-100mm		
	Install body material	Aluminium alloy		
	Charging time	6 hours of effectively sun light		
	Working time	Light 10 to 12 hours every day, sustainable 3-7 rainy day		
	Switching mode	Time control + Light sensor control + motion sensor control		
	Certification	CE. ROHS		
	Size	Product size : L1400*540*H140mm Packing Size : 145*58*18.5cm 1pcs/carton		
Weight	Net weight : 23KG Gross weight : 25KG			
Warranty	3 years warranty			

PJU 2 IN ONE

SOLAR STREET LIGHT (SPLIT - SYSTEM)

■ 2 IN ONE - 60 WATT



Light Source	: Philips SMD3030, 5000K CCT (Optional CCT 2700K, 3000K, 4000K, 6500K)
Light Unit Size	: 625*285*90mm
LED Power Rating	: 60W
Number of LEDs	: 98pcs
Efficiency	: >160 Lm / Watt
Operation Mode	: 1-2H : 100% 3-6h : 70% 7-12H : 50%
Luminous Flux	: >9600LM
Operating Temperature	: -10°C - 50°C
LED Lifespan	: >50.000 Hours
Housing Material	: Die-cast Aluminium
IP Rating	: IP66
Battery Capacity	: 12.8V 63Ah LifePO4 battery
Light Unit Tilt	: 0°-270°
Finish	: RAL 9016 Traffic White
Sensor Detection Area	: Up to 10 m to either side, i.e 20 m Pole spacing (Typical Height: 6m-10m)
Gross Weight	: 9Kg

■ 2 IN ONE - 80 WATT



Light Source	: Philips SMD3030, 5000K CCT (Optional CCT 2700K, 3000K, 4000K, 6500K)
Light Unit Size	: 625*285*90mm
LED Power Rating	: 80W
Number of LEDs	: 98pcs
Efficiency	: >160 Lm / Watt
Operation Mode	: 1-2H : 100% 3-5h : 70% 6-12H : 50%
Luminous Flux	: >12800LM
Operating Temperature	: -10°C - 50°C
LED Lifespan	: >50.000 Hours
Housing Material	: Die-cast Aluminium
IP Rating	: IP66
Battery Capacity	: 25.2V 35Ah Lithium battery
Light Unit Tilt	: 0°-270°
Finish	: RAL 9016 Traffic White
Sensor Detection Area	: Up to 10 m to either side, i.e 20 m Pole spacing (Typical Height: 6m-10m)
Gross Weight	: 9.2Kg

■ 2 IN ONE - 100 WATT



Light Source	: Philips SMD3030, 5000K CCT (Optional CCT 2700K, 3000K, 4000K, 6500K)
Light Unit Size	: 710*285*90mm
LED Power Rating	: 100W
Number of LEDs	: 144pcs
Efficiency	: >160 Lm / Watt
Operation Mode	: 1-2H : 100% 3-5H : 70% 6-12H : 50%
Luminous Flux	: >16000LM
Operating Temperature	: -10°C - 50°C
LED Lifespan	: >50.000 Hours
Housing Material	: Die-cast Aluminium
IP Rating	: IP66
Battery Capacity	: 25.2V 40Ah Lithium battery
Light Unit Tilt	: 0°-270°
Finish	: RAL 9016 Traffic White
Sensor Detection Area	: Up to 10 m to either side, i.e 20 m Pole spacing (Typical Height: 6m-10m)
Gross Weight	: 12Kg